

EVDO/CDMA Wireless Card

High Performance Low Power consumption



Features & Functions

Enjoy High Speed Internet Suring With Mobility!

Introduction:

EVDO Technical Parameters:

EVDO 800 ○/450 ○/1900 ○ Mhz band
Data Transmission up to 2.5Mbps ○ or 3.1 Mbps ○
Forward Link : Up to 2.4Mbps ○ or 3.1 Mbps ○
Reverse Link : Up to 153Kbps ○ or 1.8Mbps ○
Support RUIM ○ NON-RUIM ○
CDMA Max < 700mA CDMA Typical < 300mA
Sleep < 50mA

CDMA Technical Parameters:

CDMA2000 1x RTT 800 ○/1900 ○/450 ○ Mhz band
Data Transmission up to 153.6kbps
R-UIM application toolkit

Features and Operate system:

Supply voltage range 3.3 V
Low power consumption
External removable antenna.
Operating System: Windows2000/XP/vista32 ○/ vista64 ○/MAC OS ○
Control via AT-Command (S-707, AT command set), IS-683A compliant over-air download/update capabilities
Interface: PCMCIA ○/USB2.0 ○/EXPRESS-T ○
Operation Temperature: -30 °C to +60 °C
Restricted Operation temperature: -35 °C to -30 °C and +60 °C to +70 °C

Remark:

1. Unit Price Term: FOB Taiwan or HK.
2. Delivery Time: 15-20 work days after received your 30% deposit.
3. Payment Term: 30% deposit first, The balance 70% T/T before the shipment.