

# ***EVDO/CDMA Wireless Card***

**High Performance Low Power consumption**



**CU-3**

**EVDO  
CDMA Wireless Card**

## **Features & Functions**

### **Enjoy High Speed Internet Suring With Mobility!**

#### **Introduction:**

##### **EVDO Technical Parameters:**

EVDO 800 ○/450 ○/1900 ○ Mhz band  
Data Transmission up to 2.5Mbps ○ or 3.1 Mbps ○  
Forward Link : Up to 2.4Mbps ○ or 3.1 Mbps ○  
Reverse Link : Up to 153Kbps ○ or 1.8Mbps ○  
Support RUIIM ○ NON-RUIIM ○  
CDMA Max < 700mA CDMA Typical < 300mA  
Sleep < 50mA

##### **CDMA Technical Parameters:**

CDMA2000 1×RTT 800 ○/1900 ○/450 ○ Mhz band  
Data Transmission up to 153.6kbps  
R-UIM application toolkit

#### **Features and Operate system:**

Supply voltage range 3.3 V  
Low power consumption  
External removable antenna.  
Operating System: Windows2000/XP/vista32 ○/ vista64 ○/MAC OS ○  
Control via AT-Command (S-707, AT command set), IS-683A compliant over-air download/update capabilities  
Interface: PCMCIA ○/USB2.0 ○/EXPRESS-T ○  
Operation Temperature: -30 °C to +60 °C  
Restricted Operation temperature: -35 °C to -30 °C and +60 °C to +70 °C

#### **Remark:**

1. Unit Price Term: FOB Taiwan or HK.
2. Delivery Time: 15-20 work days after received your 30% deposit.
3. Payment Term: 30% deposit first, The balance 70% T/T before the shipment.